

CATALOG SUMMARY

Table of Contents

| | |
|-------------------------|----|
| Table of Contents | 1 |
| Warranty | 17 |

Product Line Overview

| | |
|--|----|
| Hydraulic Hose, Fittings, Crimpers | 18 |
|--|----|

Hose

| | |
|--|----|
| Low Pressure (<i>GR6, HR6, GR4, HR4, GR3, IG, IGTC, UG</i>) | 33 |
| Medium Pressure (<i>GR1SN, HR1SN, GFS, NSF, GR7, TR7, NR7, BR7</i>) | 41 |
| High Pressure (<i>GR2SN, HR2SN, LR2SN, CR2SN, GR8, TR8, NR8, GR16, GR16SC, AR16SC, GR17, AR17, GCP3, GR18</i>) | 49 |
| Very High Pressure (<i>GR12, AR12, GR13, AR13, GR15, AR15, G4SP, G4SH</i>) | 63 |
| Special Application (<i>GR5, HR5, GUT, GR14A, GGUN, GHJ</i>) | 71 |
| Air Conditioning Hose (<i>G4826, G4867, G4890</i>) | 77 |

Fittings

| | |
|--|-----|
| Section 1 (<i>fittings for hoses: GR1SN, HR1SN, GFS, GR2SN, HR2SN, LR2SN, CR2SN, GR16, GR16SC, AR16SC, GCP3</i>) | 91 |
| Section 2 (<i>fittings for hoses: GR17, AR17</i>) | 129 |
| Section 3 (<i>fittings for hoses: GR7, TR7, NR7, BR7, GR8, TR8, NR8, GR18</i>) | 165 |
| Section 4 (<i>fittings for hoses: GR12, AR12</i>) | 182 |
| Section 5 (<i>fittings for hoses: GR13, AR13, GR15, AR15, G4SP, G4SH</i>) | 209 |
| Section 6 (<i>fittings for hoses: GR3, GR4, HR4, GR6, HR6, GR14A</i>) | 242 |
| Section 7 (<i>fittings for hoses: GR5, HR5</i>) | 272 |
| Section 8 (<i>fittings for hoses: NSF, GGUN, GHJ, IG, IGTC, UG</i>) | 303 |
| Section 9 (Air Conditioning) (<i>fittings and adapters for hoses: G4826, G4867, G4890</i>) | 308 |
| Section 10 (Ferrules) | 338 |

| | |
|-----------------------|-----|
| Adapters | 353 |
|-----------------------|-----|

Equipment and Accessories

| | |
|---|-----|
| Crimpers, Saws, Skivers, Cabinets | 461 |
|---|-----|

Assemblies

| | |
|--|-----|
| Defining Assembly Length, Steps in Hose Assembly | 472 |
|--|-----|

Installation and Maintenance

| | |
|--|-----|
| Safety Considerations, Proper Installation, Hose Maintenance and Storage | 487 |
|--|-----|

Appendix

| | |
|--|-----|
| Fitting Identification, Pressure Tables, Conversion Tables, Alphanumeric Index | 493 |
|--|-----|

©2006 Goodyear Tire & Rubber Company. All Rights Reserved.

DETAILED CONTENTS

Table of Contents

| | |
|-------------------|----|
| Table of Contents | 1 |
| Warranty | 17 |

Overview

| | |
|----------------------|----|
| Perma-Crimp™ Hose | 24 |
| Perma-Crimp Fittings | 28 |
| Perma-Crimp Crimpers | 30 |

Hose

| | |
|--------------------------------------|----|
| Goodyear Hydraulic Hose Nomenclature | 31 |
|--------------------------------------|----|

LOW PRESSURE

| | |
|--------------------------------|----|
| GR6 - SAE 100R6/854 R6 | 33 |
| HR6 - DESERT™ SAE 100R6/854 R6 | 34 |
| GR4 - SAE 100R4 | 35 |
| HR4 - DESERT SAE 100R4 | 36 |
| GR3 - SAE 100R3/EN 854 R3 | 37 |
| IG - INSTA-GRIP™ 300 | 38 |
| IGTC - INSTA-GRIP™ TC | 39 |
| UG - ULTRA-GRIP™ | 40 |

MEDIUM PRESSURE

| | |
|---|----|
| GR1SN - SAE 100R1AT/1SN | 41 |
| HR1SN - DESERT SAE 100R1AT/1SN | 42 |
| GFS - SAE 100R1AT/1SN (Fire Suppression) | 43 |
| NSFX - SAFLEX® | 44 |
| GR7 - SAE 100R7/855 R7 | 45 |
| TR7 - SAE 100R7 (Twin-Line) | 46 |
| NR7 - SAE 100R7 (Non-Conductive) | 47 |
| BR7 - SAE 100R7 (Twin-Line, Non-Conductive) | 48 |

HIGH PRESSURE

| | |
|---------------------------------------|----|
| GR2SN - SAE 100R2AT/2SN | 49 |
| HR2SN - DESERT SAE 100R2AT/2SN | 50 |
| LR2SN - ARCTIC™ SAE 100R2AT/2SN | 51 |
| CR2SN - ARMORCOAT™ SAE 100R2AT/2SN | 52 |
| GR8 - SAE 100R8/855 R8 | 53 |
| TR8 - SAE 100R8 (Twin-Line) | 54 |
| NR8 - SAE 100R8 (Non-Conductive) | 55 |
| GR16 - SAE 100R16 | 56 |
| GR16SC - SAE 100R16/857 2SC | 57 |
| AR16SC - ARMORCOAT SAE 100R16/857 2SC | 58 |
| GR17 - SAE 100R17 | 59 |
| AR17 - ARMORCOAT SAE 100R17 | 60 |
| GCP3 - SAE 100R17 (Constant Pressure) | 61 |
| GR18 - SAE 100R18 | 62 |

VERY HIGH PRESSURE

| | |
|-------------------------------------|----|
| GR12 - SAE 100R12/856 12 | 63 |
| AR12 - ARMORCOAT SAE 100R12/856 R12 | 64 |
| GR13 - SAE 100R13/856 R13 | 65 |
| AR13 - ARMORCOAT SAE 100R13/856 R13 | 66 |
| GR15 - SAE 100R15 | 67 |
| AR15 - ARMORCOAT SAE 100R15 | 68 |
| G4SP - EN 856 4SP/DIN 20023 4SP | 69 |
| G4SH - EN 856 4SH/DIN 20023 4SH | 70 |

SPECIAL APPLICATION

| | |
|------------------------|----|
| GR5 - SAE 100R5 | 71 |
| HR5 - DESERT SAE 100R5 | 72 |
| GUT - J1402 AI | 73 |
| GR14A - SAE 100R14A | 74 |
| GGUN - GREASE GUN HOSE | 75 |
| GHJ - JACK HOSE | 76 |

AIR CONDITIONING

| | |
|----------------------|----|
| G4826 - GALAXY® 4826 | 77 |
| G4867 - GALAXY 4867 | 78 |
| G4890 - GALAXY 4890 | 79 |

| | |
|---------------------------------------|----|
| Hose Working Pressure Selection Guide | 80 |
|---------------------------------------|----|

TABLE OF CONTENTS

| | |
|--|-----|
| Goodyear Hydraulic Hose Special Attributes | .82 |
| Hose Temperature Limits | .83 |
| Hose Accessories | .84 |
| Protective Sleeving | .84 |
| Protective Wraps | .84 |

Fittings

| | |
|---|-----|
| Goodyear Hydraulic Fitting Nomenclature | .86 |
| Goodyear Hydraulic Ferrule Nomenclature | .88 |
| Perma-Crimp Fitting Selection | .89 |

FITTINGS SECTION 1

(Fittings for hoses: GR1SN, HR1SN, GFS, GR2SN, HR2SN, LR2SN, CR2SN, GR16, GR16SC, AR16SC, GCP3)

| | |
|---|-----|
| JIC 37° | |
| JIC 37°, Female, Swivel (JCFX) | .92 |
| JIC 37°, Female, 45° Elbow, Swivel (JCFX45) | .93 |
| JIC 37°, Female, 90° Elbow, Swivel (JCFX90, JCFX90L, JCFX90S) | .94 |
| JIC 37°, Male (JCM) | .95 |
| SAE 45° Flare | |
| SAE 45°, Female, Swivel (SFFX) | .96 |
| SAE 45°, Female, 45° Elbow, Swivel (SFFX45) | .96 |
| SAE 45°, Female, 90° Elbow, Swivel (SFFX90, SFFX90L) | .97 |
| SAE 45°, Male (SFM) | .97 |
| SAE 45° Inverted Flare | |
| SAE 45° Inverted Flare, Male, Swivel (SIMX) | .98 |
| SAE 45° Inverted Flare, Male, 45° Elbow, Swivel (SIMX45) | .98 |
| SAE 45° Inverted Flare, Male, 90° Elbow, Swivel (SIMX90) | .99 |
| NPTF | |
| NPTF, Female (NPF) | .99 |
| NPTF, Female, Swivel (NPFX) | 100 |
| NPTF, Male (NPM) | 101 |
| NPTF, Male, Swivel (NPMX) | 102 |
| NPTF, Male, 90° Elbow (Block) Swivel (NPMX90B) | 102 |
| NPSM | |
| NPSM, Female, Swivel (NSEFX) | 103 |
| Grease Tap | |
| Grease Tap, Female (GTF) | 103 |
| Flareless Tube Fitting | |
| Flareless Tube Fitting, Male (FTM) | 104 |
| Standpipe | |
| Standpipe (SP) | 104 |
| Standpipe, 45° Elbow (SP45) | 105 |
| O-Ring Face Seal | |
| ORFS, Female, Swivel (OFFX) | 105 |
| ORFS, Female, 45° Elbow, Swivel (OFFX45) | 106 |
| ORFS, Female, 90° Elbow, Swivel (OFFX90, OFFX90L, OFFX90S) | 107 |
| ORFS, Male (OFM) | 108 |
| O-Ring Boss | |
| OR Boss, Male (OBM) | 109 |
| OR Boss, Male, Swivel (OBMX) | 110 |
| OR Boss, Male, 90° Elbow (Block) Swivel (OBMX90B) | 110 |
| Code 61 | |
| Code 61 (FL) | 111 |
| Code 61, 22.5° Elbow (FL22) | 111 |
| Code 61, 30° Elbow (FL30) | 112 |
| Code 61, 45° Elbow (FL45) | 112 |
| Code 61, 60° Elbow (FL60) | 113 |
| Code 61, 67° Elbow (FL67) | 113 |
| Code 61, 90° Elbow (FL90) | 114 |
| Code 62 | |
| Code 62 (FH) | 114 |
| Code 62, 22.5° Elbow (FH22) | 115 |
| Code 62, 30° Elbow (FH30) | 115 |
| Code 62, 45° Elbow (FH45) | 116 |
| Code 62, 60° Elbow (FH60) | 116 |
| Code 62, 90° Elbow (FH90) | 117 |
| Komatsu Flange | |
| Komatsu Flange (KF) | 117 |
| Komatsu Flange, 45° Elbow (KF45) | 118 |
| Komatsu Flange, 90° Elbow (KF90) | 118 |



One Source, One System, One Solution.

www.hydraulics.goodyear.com

Information in this catalog supersedes all previously printed material and is current as of September 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online. Complete product warranty and terms of sale information can be found on the last pages of this catalog.

TABLE OF CONTENTS

| | |
|---|-----|
| BSPP | |
| BSPP, Female, Swivel (BPFX) | 119 |
| BSPP, Female, 45° Elbow, Swivel (BPFX45) | 119 |
| BSPP, Female, 90° Elbow, Swivel (BPFX90) | 120 |
| BSPP, Male (BPM) | 120 |
| BSPT | |
| BSPT, Male (BTM) | 121 |
| BSP Flat Seat | |
| BSP Flat Seat, Female, Swivel (BFFX) | 121 |
| DIN 24° Light | |
| DIN 24°L, Female, Swivel (DLFX) | 122 |
| DIN 24°L, Female, 45° Elbow, Swivel (DLFX45) | 122 |
| DIN 24°L, Female, 90° Elbow, Swivel (DLFX90) | 123 |
| DIN 24°L, Male (DLM) | 123 |
| DIN 24° Heavy | |
| DIN 24°H, Female, Swivel (DHFX) | 124 |
| DIN 24°H, Female, 45° Elbow, Swivel (DHFX45) | 124 |
| DIN 24°H, Female, 90° Elbow, Swivel (DHFX90) | 125 |
| DIN 24°H, Male (DHM) | 125 |
| DIN 60° | |
| DIN 60°, Female, 45° Elbow, Swivel (DNFX45) | 126 |
| DIN 60°, Female, 90° Elbow, Swivel (DNFX90) | 126 |
| Komatsu 30° Metric | |
| Komatsu 30° Metric, Female, Swivel (KMFx) | 127 |
| Komatsu 30° Metric, Female, 45° Elbow, Swivel (KMFx45) | 127 |
| Komatsu 30° Metric, Female, 90° Elbow, Swivel (KMFx90) | 128 |
| JIS 30° | |
| JIS 30°, Female, Swivel (JSFX) | 128 |
| FITTING SECTION 2 | |
| (Fittings for hoses: GR17, AR17) | |
| JIC 37° | |
| JIC 37°, Female, Swivel (JCFX) | 130 |
| JIC 37°, Female, 45° Elbow, Swivel (JCFX45) | 131 |
| JIC 37°, Female, 90° Elbow, Swivel (JCFX90, JCFX90L, JCFX90S) | 132 |
| JIC 37°, Male (JCM) | 133 |
| SAE 45° Flare | |
| SAE 45°, Female, Swivel (SFFX) | 134 |
| SAE 45°, Female, 45° Elbow, Swivel (SFFX45) | 134 |
| SAE 45°, Female, 90° Elbow, Swivel (SFFX90, SFFX90L) | 135 |
| SAE 45°, Male, (SFM) | 135 |
| SAE 45° Inverted Flare | |
| SAE 45° Inverted Flare, Male, Swivel (SIMX) | 136 |
| SAE 45° Inverted Flare, Male, 45° Elbow, Swivel (SIMX45) | 136 |
| SAE 45° Inverted Flare, Male, 90° Elbow, Swivel (SIMX90) | 137 |
| NPTF | |
| NPTF, Female (NPF) | 137 |
| NPTF, Female, Swivel (NPFx) | 138 |
| NPTF, Male (NPM) | 139 |
| NPTF, Male, Swivel (NPMx) | 140 |
| NPTF, Male, 90° Elbow (Block) Swivel (NPMx90B) | 140 |
| NPSM | |
| NPSM, Female, Swivel (NSFX) | 141 |
| Flareless Tube Fitting | |
| Flareless Tube Fitting, Male (FTM) | 141 |
| Standpipe | |
| Standpipe (SP) | 142 |
| Standpipe, 45° Elbow (SP45) | 142 |
| O-Ring Face Seal | |
| ORFS, Female, Swivel (OFFX) | 143 |
| ORFS, Female, 45° Elbow, Swivel (OFFX45) | 144 |
| ORFS, Female, 90° Elbow, Swivel (OFFX90, OFFX90L, OFFX90S) | 145 |
| ORFS, Male (OFM) | 146 |
| O-Ring Boss | |
| OR Boss, Male (OBM) | 147 |
| OR Boss, Male, Swivel (OBMx) | 148 |
| OR Boss, Male, 90° Elbow (Block) Swivel (OBMx90B) | 148 |
| Code 61 | |
| Code 61 (FL) | 149 |
| Code 61, 22.5° Elbow (FL22) | 149 |
| Code 61, 30° Elbow (FL30) | 150 |

TABLE OF CONTENTS

| | |
|--|-----|
| Code 61, 45° Elbow (FL45) | 150 |
| Code 61, 60° Elbow (FL60) | 151 |
| Code 61, 67° Elbow (FL67) | 151 |
| Code 61, 90° Elbow (FL90) | 151 |
| Code 62 | |
| Code 62 (FH) | 152 |
| Code 62, 45° Elbow (FH45) | 152 |
| Code 62, 90° Elbow (FH90) | 153 |
| Komatsu Flange | |
| Komatsu Flange (KF) | 153 |
| Komatsu Flange, 45° Elbow (KF45) | 153 |
| Komatsu Flange, 90° Elbow (KF90) | 154 |
| BSPP | |
| BSPP, Female, Swivel (BPFX) | 154 |
| BSPP, Female, 45° Elbow, Swivel (BPFX45) | 155 |
| BSPP, Female, 90° Elbow, Swivel (BPFX90) | 155 |
| BSPP, Male (BPM) | 156 |
| BSPT | |
| BSPT, Male (BTM) | 156 |
| BSP Flat Seat | |
| BSP Flat Seat, Female, Swivel (BFFX) | 157 |
| DIN 24° Light | |
| DIN 24°L, Female, Swivel (DLFX) | 157 |
| DIN 24°L, Female, 45° Elbow, Swivel (DLFX45) | 158 |
| DIN 24°L, Female, 90° Elbow, Swivel (DLFX90) | 158 |
| DIN 24°L, Male (DLM) | 159 |
| DIN 24° Heavy | |
| DIN 24°H, Female, Swivel (DHFX) | 159 |
| DIN 24°H, Female, 45° Elbow, Swivel (DHFX45) | 160 |
| DIN 24°H, Female, 90° Elbow, Swivel (DHFX90) | 160 |
| DIN 24°H, Male (DHM) | 161 |
| DIN 60° | |
| DIN 60°, Female, 45° Elbow, Swivel (DNFX45) | 161 |
| DIN 60°, Female, 90° Elbow, Swivel (DNFX90) | 162 |
| Komatsu 30° Metric | |
| Komatsu 30° Metric, Female, Swivel (KMFx) | 162 |
| Komatsu 30° Metric, Female, 45° Elbow, Swivel (KMFx45) | 163 |
| Komatsu 30° Metric, Female, 90° Elbow, Swivel (KMFx90) | 163 |
| JIS 30° | |
| JIS 30°, Female, Swivel (JSFX) | 164 |

FITTING SECTION 3

(Fittings for hoses: GR7, TR7, NR7, BR7, GR8, TR8, NR8, GR18)

| | |
|--|-----|
| JIC 37° | |
| JIC 37°, Female, Swivel (JCFX) | 166 |
| JIC 37°, Female, 45° Elbow, Swivel (JCFX45) | 167 |
| JIC 37°, Female, 90° Elbow, Swivel (JCFX90, JCFX90L) | 168 |
| JIC 37°, Male (JCM) | 169 |
| SAE 45° Flare | |
| SAE 45°, Female, Swivel (SFFX) | 170 |
| SAE 45°, Female, 90° Elbow, Swivel (SFFX90) | 170 |
| SAE 45° Inverted Flare | |
| SAE 45° Inverted Flare, Male, Swivel (SIMX) | 171 |
| SAE 45° Inverted Flare, Male, 45° Elbow, Swivel (SIMX45) | 171 |
| SAE 45° Inverted Flare, Male, 90° Elbow, Swivel (SIMX90) | 172 |
| NPTF | |
| NPTF, Female (NPF) | 172 |
| NPTF, Male (NPM) | 173 |
| NPTF, Male, Swivel (NPMX) | 174 |
| NPSM | |
| NPSM, Female, Swivel (NSEFX) | 174 |
| Flareless Tube Fitting | |
| Flareless Tube Fitting, Male (FTM) | 175 |
| Standpipe | |
| Standpipe, 45° Elbow (SP45) | 175 |
| O-Ring Face Seal | |
| ORFS, Female, Swivel (OFFX) | 176 |
| ORFS, Female, 45° Elbow, Swivel (OFFX45) | 176 |
| ORFS, Female, 90° Elbow, Swivel (OFFX90, OFFX90L) | 177 |
| ORFS, Male (OFM) | 177 |



TABLE OF CONTENTS

| | |
|--|-----|
| O-Ring Boss | |
| OR Boss, Male (OBM) | 178 |
| OR Boss, Male, Swivel (OBMX) | 178 |
| OR Boss, Male, 90° Elbow (Block), Swivel (OBMX90B) | 179 |
| BSPP | |
| BSPP, Female, Swivel (BPFX) | 179 |
| BSPP, Female, 90° Elbow, Swivel (BPFX90) | 180 |
| DIN 60° | |
| DIN 60°, Female, 90° Elbow, Swivel (DNFX90) | 180 |
| JIS 30° | |
| JIS 30°, Female, Swivel (JSFX) | 181 |

FITTING SECTION 4

(Fittings for hoses: GR12, AR12)

| | |
|---|-----|
| JIC 37° | |
| JIC 37°, Female, Swivel (JCFX) | 183 |
| JIC 37°, Female, 45° Elbow, Swivel (JCFX45) | 184 |
| JIC 37°, Female, 90° Elbow, Swivel (JCFX90, JCFX90L, JCFX90S) | 185 |
| JIC 37°, Male (JCM) | 186 |
| NPTF | |
| NPTF, Male (NPM) | 187 |
| NPTF, Male, Swivel (NPMX) | 188 |
| NPSM | |
| NPSM, Female, Swivel (NSFX) | 188 |
| O-Ring Face Seal | |
| ORFS, Female, Swivel (OFFX) | 189 |
| ORFS, Female, 45° Elbow, Swivel (OFFX45) | 190 |
| ORFS, Female, 90° Elbow, Swivel (OFFX90, OFFX90L, OFFX90S) | 191 |
| ORFS, Male (OFM) | 192 |
| O-Ring Boss | |
| OR Boss, Male (OBM) | 192 |
| Code 61 | |
| Code 61 (FL) | 193 |
| Code 61, 22.5° Elbow (FL22) | 193 |
| Code 61, 30° Elbow (FL30) | 194 |
| Code 61, 45° Elbow (FL45) | 194 |
| Code 61, 60° Elbow (FL60) | 195 |
| Code 61, 67° Elbow (FL67) | 195 |
| Code 61, 90° Elbow (FL90, FL90L) | 196 |
| Code 62 | |
| Code 62 (FH) | 197 |
| Code 62, 22.5° Elbow (FH22) | 197 |
| Code 62, 30° Elbow (FH30) | 198 |
| Code 62, 45° Elbow (FH45) | 198 |
| Code 62, 60° Elbow (FH60) | 199 |
| Code 62, 67° Elbow (FH67) | 199 |
| Code 62, 90° Elbow (FH90) | 200 |
| Caterpillar Flange | |
| Caterpillar Flange (CF) | 200 |
| Caterpillar Flange, 45° Elbow (CF45) | 201 |
| Caterpillar Flange, 90° Elbow (CF90) | 201 |
| BSPP | |
| BSPP, Female, Swivel (BPFX) | 202 |
| BSPP, Female, 45° Elbow, Swivel (BPFX45) | 202 |
| BSPP, Female, 90° Elbow, Swivel (BPFX90) | 203 |
| BSPP, Male (BPM) | 203 |
| BSPT | |
| BSPT, Male (BTM) | 204 |
| DIN 24° Light | |
| DIN 24°L, Female, Swivel (DLFX) | 204 |
| DIN 24°L, Female, 90° Elbow, Swivel (DLEX90) | 205 |
| DIN 24° Heavy | |
| DIN 24°H, Female, Swivel (DHFX) | 205 |
| DIN 24°H, Female, 45° Elbow, Swivel (DHFX45) | 206 |
| DIN 24°H, Female, 90° Elbow, Swivel (DHFX90) | 206 |
| DIN 24°H, Male (DHM) | 207 |
| Komatsu 30° Metric | |
| Komatsu 30° Metric, Female, Swivel (KMFX) | 207 |
| JIS 30° | |
| JIS 30°, Female, Swivel (JSFX) | 208 |

TABLE OF CONTENTS

FITTING SECTION 5

(Fittings for hoses: GR13, AR13, GR15, AR15, G4SP, G4SH)

| | |
|---|-----|
| JIC 37° | |
| JIC 37°, Female, Swivel (JCFX) | 210 |
| JIC 37°, Female, 45° Elbow, Swivel (JCFX45) | 211 |
| JIC 37°, Female, 90° Elbow, Swivel (JCFX90, JCFX90L, JCFX90S) | 212 |
| JIC 37°, Male (JCM) | 213 |
| SAE 45° Flare | |
| SAE 45°, Female, Swivel (SFFX) | 214 |
| NPTF | |
| NPTF, Female (NPF) | 214 |
| NPTF, Male (NPM) | 215 |
| NPTF, Male, Swivel (NPMX) | 216 |
| NPT | |
| NPT, Male, API (NPMAPI) | 216 |
| NPSM | |
| NPSM, Female, Swivel (NSEFX) | 217 |
| Flareless Tube Fitting | |
| Flareless Tube Fitting, Male (FTM) | 217 |
| Standpipe | |
| Standpipe (SP) | 218 |
| Standpipe, 45° Elbow (SP45) | 218 |
| O-Ring Face Seal | |
| ORFS, Female, Swivel (OFFX) | 219 |
| ORFS, Female, 45° Elbow, Swivel (OFFX45) | 220 |
| ORFS, Female, 90° Elbow, Swivel (OFFX90, OFFX90L, OFFX90S) | 221 |
| ORFS, Male (OFM) | 222 |
| O-Ring Boss | |
| OR Boss, Male (OBM) | 222 |
| Code 61 | |
| Code 61 (FL) | 223 |
| Code 61, 22.5° Elbow (FL22) | 223 |
| Code 61, 30° Elbow (FL30) | 224 |
| Code 61, 45° Elbow (FL45) | 224 |
| Code 61, 60° Elbow (FL60) | 225 |
| Code 61, 67° Elbow (FL67) | 225 |
| Code 61, 90° Elbow (FL90) | 226 |
| Code 62 | |
| Code 62 (FH) | 227 |
| Code 62, 22.5° Elbow (FH22) | 227 |
| Code 62, 30° Elbow (FH30) | 228 |
| Code 62, 45° Elbow (FH45) | 228 |
| Code 62, 60° Elbow (FH60) | 229 |
| Code 62, 67° Elbow (FH67) | 229 |
| Code 62, 90° Elbow (FH90) | 230 |
| Caterpillar Flange | |
| Caterpillar Flange (CF) | 230 |
| Caterpillar Flange, 22.5° Elbow (CF22) | 231 |
| Caterpillar Flange, 30° Elbow (CF30) | 231 |
| Caterpillar Flange, 45° Elbow (CF45) | 231 |
| Caterpillar Flange, 60° Elbow (CF60) | 232 |
| Caterpillar Flange, 90° Elbow (CF90, CF90L) | 232 |
| BSPP | |
| BSPP, Female, Swivel (BPFX) | 233 |
| BSPP, Female, 45° Elbow, Swivel (BPFX45) | 233 |
| BSPP, Female, 90° Elbow, Swivel (BPFX90) | 234 |
| BSPP, Male (BPM) | 234 |
| BSPT | |
| BSPT, Male (BTM) | 235 |
| BSP Flat Seat | |
| BSP Flat Seat, Female, Swivel (BFFX) | 235 |
| DIN 24° Light | |
| DIN 24°L, Female, Swivel (DLFX) | 236 |
| DIN 24°L, Female, 45° Elbow, Swivel (DLFX45) | 236 |
| DIN 24°L, Female, 90° Elbow, Swivel (DLFX90) | 237 |
| DIN 24°L, Male (DLM) | 237 |
| DIN 24° Heavy | |
| DIN 24°H, Female, Swivel (DHFX) | 238 |
| DIN 24°H, Female, 45° Elbow, Swivel (DHFX45) | 238 |
| DIN 24°H, Female, 90° Elbow, Swivel (DHFX90) | 239 |

TABLE OF CONTENTS

| | |
|---|-----|
| DIN 24°H, Male (DHM) | 239 |
| DIN 60° | |
| DIN 60°, Female, 45° Elbow, Swivel (DNFX45) | 240 |
| DIN 60°, Female, 90° Elbow, Swivel (DNFX90) | 240 |
| Komatsu 30° Metric | |
| Komatsu 30° Metric, Female, Swivel (KMFY) | 241 |
| JIS 30° | |
| JIS 30°, Female, Swivel (JSFY) | 241 |
| FITTING SECTION 6 | |
| <i>(Fittings for hoses: GR3, GR4, HR4, GR6, HR6, GR14A)</i> | |
| JIC 37° | |
| JIC 37°, Female, Swivel (JCFY) | 243 |
| JIC 37°, Female, 45° Elbow, Swivel (JCFY45) | 244 |
| JIC 37°, Female, 90° Elbow, Swivel (JCFY90, JCFY90L, JCFY90S) | 245 |
| JIC 37°, Male (JCM) | 246 |
| SAE 45° Flare | |
| SAE 45°, Female, Swivel (SFFY) | 246 |
| SAE 45°, Female, 45° Elbow, Swivel (SFFY45) | 247 |
| SAE 45°, Female, 90° Elbow, Swivel (SFFY90, SFFY90L) | 247 |
| SAE 45°, Male, (SFM) | 247 |
| SAE 45° Inverted Flare | |
| SAE 45° Inverted Flare, Male, Swivel (SIMY) | 248 |
| SAE 45° Inverted Flare, Male, 45° Elbow, Swivel (SIMY45) | 248 |
| SAE 45° Inverted Flare, Male, 90° Elbow, Swivel (SIMY90) | 249 |
| NPTF | |
| NPTF, Female (NPF) | 249 |
| NPTF, Male (NPM) | 250 |
| NPTF, Male, Swivel (NPMY) | 250 |
| NPTF, Male, 90° Elbow (Block) Swivel (NPMY90B) | 251 |
| NPSM | |
| NPSM, Female, Swivel (NSFY) | 251 |
| Flareless Tube Fitting | |
| Flareless Tube Fitting, Male (FTM) | 252 |
| Standpipe | |
| Standpipe (SP) | 252 |
| Standpipe, 45° Elbow (SP45) | 253 |
| O-Ring Face Seal | |
| ORFS, Female, Swivel (OFFY) | 253 |
| ORFS, Female, 45° Elbow, Swivel (OFFY45) | 254 |
| ORFS, Female, 90° Elbow, Swivel (OFFY90, OFFY90L, OFFY90S) | 255 |
| ORFS, Male (OFM) | 256 |
| O-Ring Boss | |
| OR Boss, Male (OBM) | 256 |
| OR Boss, Male, Swivel (OBMY) | 257 |
| OR Boss, Male, 90° Elbow (Block) Swivel (OBMY90B) | 257 |
| Code 61 | |
| Code 61 (FL) | 258 |
| Code 61, 22.5° Elbow (FL22) | 258 |
| Code 61, 30° Elbow (FL30) | 259 |
| Code 61, 45° Elbow (FL45) | 259 |
| Code 61, 60° Elbow (FL60) | 260 |
| Code 61, 90° Elbow (FL90) | 260 |
| Code 62 | |
| Code 62 (FH) | 261 |
| Code 62, 45° Elbow (FH45) | 261 |
| Code 62, 90° Elbow (FH90) | 262 |
| BSPP | |
| BSPP, Female, Swivel (BPFY) | 262 |
| BSPP, Female, 45° Elbow, Swivel (BPFY45) | 263 |
| BSPP, Female, 90° Elbow, Swivel (BPFY90) | 263 |
| BSPP, Male (BPM) | 264 |
| BSPT | |
| BSPT, Male (BTM) | 264 |
| BSP Flat Seat | |
| BSP Flat Seat, Female, Swivel (BFFY) | 265 |
| DIN 24° Light | |
| DIN 24°L, Female, Swivel (DLFY) | 265 |
| DIN 24°L, Female, 45° Elbow, Swivel (DLFY45) | 266 |
| DIN 24°L, Female, 90° Elbow, Swivel (DLFY90) | 266 |
| DIN 24°L, Male (DLM) | 267 |

TABLE OF CONTENTS

| | |
|---|-----|
| DIN 24° Heavy | |
| DIN 24°H, Female, Swivel (DHFH) | 267 |
| DIN 24°H, Female, 45° Elbow, Swivel (DHFH45) | 268 |
| DIN 24°H, Female, 90° Elbow, Swivel (DHFH90) | 268 |
| DIN 24°H, Male (DHM) | 269 |
| DIN 60° | |
| DIN 60°, Female, 45° Elbow, Swivel (DNFH45) | 269 |
| DIN 60°, Female, 90° Elbow, Swivel (DNFH90) | 270 |
| Komatsu 30° Metric | |
| Komatsu 30° Metric, Female, Swivel (KMFH) | 270 |
| Komatsu 30° Metric, Female, 45° Elbow, Swivel (KMFH45) | 271 |
| Komatsu 30° Metric, Female, 90° Elbow, Swivel (KMFH90) | 271 |
| JIS 30° | |
| JIS 30°, Female, Swivel (JSFH) | 271 |
| FITTING SECTION 7 | |
| (Fittings for hoses: GR5, HR5) | |
| JIC 37° | |
| JIC 37°, Female, Swivel (JCFH) | 273 |
| JIC 37°, Female, 45° Elbow, Swivel (JCFH45) | 274 |
| JIC 37°, Female, 90° Elbow, Swivel (JCFH90, JCFH90L, JCFH90S) | 275 |
| JIC 37°, Male (JCM) | 276 |
| SAE 45° Flare | |
| SAE 45°, Female, Swivel (SFFH) | 277 |
| SAE 45°, Female, 45° Elbow, Swivel (SFFH45) | 277 |
| SAE 45°, Female, 90° Elbow, Swivel (SFFH90, SFFH90L) | 278 |
| SAE 45°, Male, (SFM) | 278 |
| SAE 45° Inverted Flare | |
| SAE 45° Inverted Flare, Male, Swivel (SIMH) | 279 |
| SAE 45° Inverted Flare, Male, 45° Elbow, Swivel (SIMH45) | 280 |
| SAE 45° Inverted Flare, Male, 90° Elbow, Swivel (SIMH90) | 280 |
| NPTF | |
| NPTF, Female (NPF) | 281 |
| NPTF, Male, (NPM) | 282 |
| NPTF, Male, Swivel (NPMH) | 283 |
| NPTF, Male, 90° Elbow (Block) Swivel (NPMH90B) | 283 |
| NPSM | |
| NPSM, Female, Swivel (NSFH) | 284 |
| Flareless Tube Fitting | |
| Flareless Tube Fitting, Male (FTM) | 284 |
| Standpipe | |
| Standpipe (SP) | 285 |
| Standpipe, 45° Elbow (SP45) | 285 |
| O-Ring Face Seal | |
| ORFS, Female, Swivel (OFFH) | 286 |
| ORFS, Female, 45° Elbow, Swivel (OFFH45) | 286 |
| ORFS, Female, 90° Elbow, Swivel (OFFH90, OFFH90L, OFFH90S) | 287 |
| ORFS, Male (OFM) | 288 |
| O-Ring Boss | |
| OR Boss, Male (OBM) | 289 |
| OR Boss, Male, Swivel (OBMH) | 290 |
| OR Boss, Male, 90° Elbow (Block) Swivel (OBMH90) | 290 |
| Code 61 | |
| Code 61 (FL) | 291 |
| Code 61, 45° Elbow (FL45) | 291 |
| Code 61, 90° Elbow (FL90) | 292 |
| Code 62 | |
| Code 62, 90° Elbow (FH90) | 292 |
| BSPP | |
| BSPP, Female, Swivel (BPFH) | 293 |
| BSPP, Female, 45° Elbow, Swivel (BPFH45) | 293 |
| BSPP, Female, 90° Elbow, Swivel (BPFH90) | 294 |
| BSPP, Male (BPM) | 294 |
| BSPT | |
| BSPT, Male (BTM) | 295 |
| BSP Flat Seat | |
| BSP Flat Seat, Female, Swivel (BFFH) | 295 |
| DIN 24° Light | |
| DIN 24°L, Female, Swivel (DLFH) | 296 |
| DIN 24°L, Female, 45° Elbow, Swivel (DLFH45) | 296 |
| DIN 24°L, Female, 90° Elbow, Swivel (DLFH90) | 297 |

TABLE OF CONTENTS

| | |
|---|-----|
| DIN 24°L, Male (DLM) | 297 |
| DIN 24° Heavy | |
| DIN 24°H, Female, Swivel (DHF) | 298 |
| DIN 24°H, Female, 45° Elbow, Swivel (DHF45) | 298 |
| DIN 24°H, Female, 90° Elbow, Swivel (DHF90) | 299 |
| DIN 24°H, Male (DHM) | 299 |
| DIN 60° | |
| DIN 60°, Female, 45° Elbow, Swivel (DNFX45) | 300 |
| DIN 60°, Female, 90° Elbow, Swivel (DNFX90) | 300 |
| Komatsu 30° Metric | |
| Komatsu 30° Metric, Female, Swivel (KMF) | 301 |
| Komatsu 30° Metric, Female, 45° Elbow, Swivel (KMF45) | 301 |
| Komatsu 30° Metric, Female, 90° Elbow, Swivel (KMF90) | 302 |
| JIS 30° | |
| JIS 30°, Female, Swivel (JSF) | 302 |

FITTING SECTION 8

(Fittings for Hoses: NSF, GGUN, GHJ, IG, IGTC, UG)

| | |
|---|-----|
| NPTF (for SAFLEX® Hose) | |
| NPTF, Male (SF-NPM) | 304 |
| NPTF (for Grease Gun Hose) | |
| NPTF, Male (GG-NPM) | 304 |
| NPTF (for Jack Hose) | |
| NPTF Male (B2-NPM) | 304 |
| Hose Mender | |
| Hose Mender (PB-HM) | 305 |
| JIC 37° | |
| JIC 37° Female, Swivel (PB-JCF) | 305 |
| JIC 37° Male (PB-JCM) | 305 |
| NPTF | |
| NPTF Female (PB-NPF) | 305 |
| NPTF Male (PB-NPM) | 306 |
| NPTF Male, 90° Elbow (PB-NPM90) | 306 |
| NPTF Male, Swivel (PB-NPMX) | 306 |
| SAE 45° Flare | |
| SAE 45° Female, Swivel (PB-SFF) | 307 |
| SAE 45° Inverted Flare | |
| SAE 45° Inverted Flare, Female (PB-SIF) | 307 |
| SAE 45° Inverted Flare, Male (PB-SIM) | 307 |

FITTING SECTION 9 – AIR CONDITIONING FITTINGS

(Crimp Fittings for Galaxy Air Conditioning Hoses: G4826, G4867)

| | |
|---|-----|
| Compressor O-Ring Tube | |
| Compressor OR Tube, Female, 45° Elbow (AC-COTF45) | 310 |
| Compressor OR Tube, Female, 90° Elbow (AC-COTF90) | 310 |
| Compressor OR Tube, Female, 90° Block Elbow (AC-COTF90B) | 310 |
| Compressor OR Tube, Female, R134a Valve, 90° Block Elbow (AC-COTF134V90B) | 310 |
| Flareless Tube | |
| Flareless Tube, Male (AC-FTM) | 311 |
| Flareless Tube, Male, 90° Block Elbow (AC-FTM90B) | 311 |
| Flareless Tube, Male, Metric (AC-FTMM) | 311 |
| O-Ring Insert | |
| OR Insert Male (AC-OIM) | 311 |
| OR Insert Male, 45° Elbow (AC-OIM45) | 312 |
| OR Insert Male, 90° Elbow (AC-OIM90) | 312 |
| OR Insert Male, Bulkhead (AC-OIMB) | 312 |
| OR Insert Male, Bulkhead, 90° Elbow (AC-OIMB90) | 312 |
| OR Insert Male, R134a Valve (AC-OIM134V) | 313 |
| OR Insert Male, R134a Valve, 90° Elbow (AC-OIM134V90) | 313 |
| O-Ring Tube | |
| OR Tube, Female, Swivel (AC-OTF) | 313 |
| OR Tube, Female, Swivel, 45° Elbow (AC-OTF45) | 313 |
| OR Tube, Female, Swivel, 90° Elbow (AC-OTF90) | 314 |
| OR Tube, Female, Swivel, 90° Block Elbow (AC-OTF90B) | 314 |
| OR Tube, Female, Swivel, 180° Elbow (AC-OTF180) | 314 |
| OR Tube, Female, Swivel, Metric (AC-OTFM) | 314 |
| OR Tube, Female, Swivel, Metric, 45° Elbow (AC-OTFM45) | 315 |
| OR Tube, Female, Swivel, Metric, 90° Elbow (AC-OTFM90) | 315 |
| OR Tube, Female, Swivel, R12 Valve (AC-OTF12V) | 315 |
| OR Tube, Female, Swivel, R12 Valve, 90° Elbow (AC-OTF12V90) | 315 |
| OR Tube, Female, Swivel, R134a Valve (AC-OTF134V) | 316 |

TABLE OF CONTENTS

| | |
|--|-----|
| OR Tube, Female, Swivel, R134a Valve, High Side (OTF134VHS) | 316 |
| OR Tube, Female, Swivel, R134a Valve, 45° Elbow (AC-OTF134V45) | 316 |
| OR Tube, Female, Swivel, R134a Valve, 90° Elbow (AC-OTF134V90) | 316 |
| OR Tube, Male, Swivel (AC-OTM) | 316 |
| OR Tube, Male, Swivel, 45° Elbow (AC-OTM45) | 317 |
| OR Tube, Male, Swivel, 90° Elbow (AC-OTM90) | 317 |
| OR Tube, Male, Swivel, Long Pilot (AC-OTMLP) | 317 |
| OR Tube, Male, Swivel, R134a Valve (AC-OTM134V) | 317 |
| OR Tube, Male, Swivel, R134a Valve, 90° Elbow (AC-OTM134V90) | 318 |
| SAE 45° Flare | |
| SAE 45° Flare, Female, Swivel (AC-SFFX) | 318 |
| SAE 45° Flare, Female, Swivel, 45° Elbow (AC-SFFX45) | 318 |
| SAE 45° Flare, Female, Swivel, 90° Elbow (AC-SFFX90) | 318 |
| SAE 45° Flare, Male (AC-SFM) | 319 |
| SAE 45° Flare, Male, 45° Elbow (AC-SFM45) | 319 |
| SAE 45° Flare, Male, 90° Elbow (AC-SFM90) | 319 |

FITTING SECTION 9 – ‘GC’ COOL CLIP FITTINGS

(Fittings for Galaxy Air Conditioning Hose G4890)

| | |
|---|-----|
| Compressor Pad Block | |
| Compressor Pad Block, R12 Valve/Switch, 90° Block Elbow (GC-CB12VS90) | 320 |
| Compressor Pad Block, R12 Valve/Switch Reversed, 90° Elbow (GC-CB12VSR90) | 320 |
| Compressor OR Tube | |
| Compressor OR Tube, Female, 45° Elbow (GC-COTF45) | 320 |
| Compressor OR Tube, Female, 90° Elbow (GC-COTF90) | 320 |
| Compressor OR Tube, Female, 90° Block Elbow (GC-COTF90B) | 320 |
| Compressor OR Tube, Female, R134a Valve, 90° Block Elbow (GC-COTF134V90B) | 321 |
| Flareless Tube | |
| Flareless Tube, Braze-On (GC-FTBO) | 321 |
| Flareless Tube, Male (GC-FTM) | 321 |
| Flareless Tube, Male, 90° Block Elbow (GC-FTM90B) | 321 |
| Flareless Tube, Male, Metric (GC-FTMM) | 322 |
| Ford Spring Lock | |
| Ford Spring Lock, Female (GC-FSLF) | 322 |
| Ford Spring Lock, Female, 45° Elbow (GC-FSLF45) | 322 |
| Ford Spring Lock, Female, 90° Elbow (GC-FSLF90) | 322 |
| Ford Spring Lock, Male (GC-FSLM) | 323 |
| Ford Spring Lock, Male, 45° Elbow (GC-FSLM45) | 323 |
| Ford Spring Lock, Male, 90° Elbow (GC-FSLM90) | 323 |
| Hose Mender | |
| Hose Mender (GC-HM) | 323 |
| Hose Mender, 90° Elbow (GC-HM90) | 324 |
| Hose Mender, 180° Elbow (GC-HM180) | 324 |
| Hose Mender, R12 Valve (GC-HM12V) | 324 |
| Hose Mender, R134a Valve (GC-HM134V) | 324 |
| Hose Mender, with Sight Glass (GC-HMSG) | 324 |
| Hose Mender, Tee (GC-HMT) | 325 |
| O-Ring Face Seal | |
| OR Face Seal, Female, Swivel (GC-OFFX) | 325 |
| OR Face Seal, Female, Swivel, 90° Elbow (GC-OFFX90) | 325 |
| O-Ring Insert Male | |
| OR Insert Male (GC-OIM) | 325 |
| OR Insert Male, 45° Elbow (GC-OIM45) | 326 |
| OR Insert Male, 90° Elbow (GC-OIM90) | 326 |
| OR Insert Male, Bulkhead (GC-OIMB) | 326 |
| OR Insert Male, Bulkhead, 90° Elbow (GC-OIMB90) | 326 |
| OR Insert Male, R134a Valve (GC-OIM134V) | 327 |
| OR Insert Male, R134a Valve, 90° Elbow (GC-OIM134V90) | 327 |
| O-Ring Tube | |
| OR Tube, Female, Swivel (GC-OTF) | 327 |
| OR Tube, Female, Swivel, 45° Elbow (GC-OTF45) | 327 |
| OR Tube, Female, Swivel, 90° Elbow (GC-OTF90) | 328 |
| OR Tube, Female, Swivel, 90° Block Elbow (GC-OTF90B) | 328 |
| OR Tube, Female, Swivel, 180° Elbow (GC-OTF180) | 328 |
| OR Tube, Female, Swivel, R12 Valve (GC-OTF12V) | 328 |
| OR Tube, Female, Swivel, R12 Valve, 90° Elbow (GC-OTF12V90) | 329 |
| OR Tube, Female, Swivel, R134a Valve (GC-OTF134V) | 329 |
| OR Tube, Female, Swivel, R134a Valve, High Side (GC-OTF134VHS) | 329 |
| OR Tube, Female, Swivel, R134a Valve, 45° Elbow (GC-OTF134V45) | 329 |
| OR Tube, Female, Swivel, R134a Valve, 90° Elbow (GC-OTF134V90) | 329 |
| OR Tube, Male, Swivel (GC-OTM) | 330 |

TABLE OF CONTENTS

| | |
|--|-----|
| OR Tube, Male, Swivel, 45° Elbow (GC-OTM45) | 330 |
| OR Tube, Male, Swivel, 90° Elbow (GC-OTM90) | 330 |
| OR Tube, Male, Swivel, Long Pilot (GC-OTMLP) | 330 |
| OR Tube, Male, Swivel, R134a Valve (GC-OTM134V) | 331 |
| OR Tube, Male, Swivel, R134a Valve, 90° Elbow (GC-OTM134V90) | 331 |
| SAE 45° Flare | |
| SAE 45° Flare, Female, Swivel (GC-SFFX) | 331 |
| SAE 45° Flare, Female, Swivel, 45° Elbow (GC-SFFX45) | 331 |
| SAE 45° Flare, Female, Swivel, 90° Elbow (GC-SFFX90) | 332 |
| SAE 45° Flare, Male (GC-SFM) | 332 |
| SAE 45° Flare, Male, 45° Elbow (GC-SFM45) | 332 |
| SAE 45° Flare, Male, 90° Elbow (GC-SFM90) | 332 |

FITTING SECTION 9 – A/C ADAPTERS

| | |
|--|-----|
| O-Ring Tube Compressor Female to O-Ring Insert Male, 90° Elbow, w/R134a Valve (AC-OTCF-OIM90-134V) | 333 |
| O-Ring Tube Female to O-Ring Insert Male w/R12 Valve (AC-OTF-OIM-12V) | 333 |
| O-Ring Tube Female to O-Ring Insert Male, 90° Elbow w/R12 Valve (AC-OTF-OIM90-12V) | 333 |
| O-Ring Tube Female to O-Ring Insert Male w/R134a Valve (AC-OTF-OIM-134V) | 334 |
| O-Ring Tube Female to O-Ring Insert Male, 90° Elbow w/R134a Valve (AC-OTF-OIM90-134V) | 334 |

FITTING SECTION 9 – A/C FITTING ACCESSORIES & ASSEMBLY TOOLS

| | |
|--|-----|
| Flareless Tube Nuts (AC-FTN) | 335 |
| Flareless Tube Sleeves (AC-FTS) | 335 |
| Flareless Tube Sleeves, Metric (AC-FTSM) | 335 |
| Inline Orifice Tubes (AC-ILOT) | 335 |
| O-Ring, for Ford Spring Lock (GC-OFSL) | 335 |
| O-Ring, for Switch (GC-OSWCH) | 336 |
| O-Ring, for Tube Fittings (AC-OTUBE) | 336 |
| Sealing Washers (AC-SWA, AC-SWCN, AC-SWCW) | 336 |
| Valve Adapters (AC-VA12V-134V) | 336 |
| Valve Caps (AC-VC12V, AC-VC134VHS, AC-VC134VLS) | 336 |
| Valve Core (AC-VCORE) | 337 |
| Metal Clip (GC-CLIP) | 337 |
| Plastic Clip Holder (GC-CLIPHLDR) | 337 |
| Clip Pliers (GC-PLIERS) | 337 |
| Hose Cutting Tool & Replacement Blades (HCT) (HCTRB) | 337 |

SECTION 10 – FERRULES

| | |
|---------------------------|-----|
| Uni-Crimp Ferrules | |
| UCF1 | 338 |
| UCF2 | 338 |
| UCF3 | 339 |
| UCF4 | 339 |
| UCF5 | 340 |
| UCF6 | 340 |
| UCF7 | 341 |
| UCF8 | 341 |
| UCF9 | 342 |
| Dual-Grip Ferrules | |
| DGF1 | 342 |
| DGF2 | 343 |

FITTING ACCESSORIES & REFERENCE CHARTS

| | |
|--|-----|
| Choosing the Correct Fittings | 344 |
| Working Pressure Chart | 345 |
| Thread Reference Chart | 346 |
| Fitting Accessories – O-Rings | 348 |
| Split Flanges | 350 |
| Code 61/Code 62/Caterpillar Flange Identification Template | 351 |
| Thread Identification Kit | 352 |

Adapters (For fitting styles: B1, B2, S4, S6, DG, UC, T7, T8, FG & PB)

| | |
|--|-----|
| Goodyear Hydraulic Adapters Nomenclature | 353 |
|--|-----|

STEEL ADAPTERS

| | |
|--|-----|
| BSPP | |
| BSPP, Female - BSPP, Female (BPF-BPF) | 354 |
| BSPP, Female - NPTF, Male (BPF-NPM) | 354 |
| BSPP, Female, Swivel - JIC 37°, Male (BPFX-JCM) | 355 |
| BSPP, Female, Swivel - JIC 37°, Male, 90° Elbow (BPFX-JCM90) | 355 |
| BSPP, Female, Swivel, Cap (BPFXC) | 355 |
| BSPP, Male - BSPP, Male, Hex Nipple (BPM-BPMHN) | 356 |



One Source, One System, One Solution.

www.hydraulics.goodyear.com

Information in this catalog supersedes all previously printed material and is current as of September 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online. Complete product warranty and terms of sale information can be found on the last pages of this catalog.

TABLE OF CONTENTS

| | |
|--|-----|
| BSPP, Male - JIC 37°, Female, Swivel (BPM-JCFX) | 357 |
| BSPP, Male - JIC 37°, Male (BPM-JCM) | 357 |
| BSPP, Male - JIC 37°, Male, 45° Elbow (BPM-JCM45) | 358 |
| BSPP, Male - JIC 37°, Male, 90° Elbow (BPM-JCM90) | 359 |
| BSPP, Male - NPTF, Female (BPM-NPF) | 359 |
| BSPP, Male - NPTF, Male (BPM-NPM) | 360 |
| BSPP, Plug (BPP) | 361 |
| BSPT | |
| BSPT, Male - JIC 37°, Male (BTM-JCM) | 361 |
| BSPT, Plug (BTP) | 362 |
| Compression Tube | |
| Compression Tube Nut (CTN) | 362 |
| Compression Tube Sleeve (CTS) | 362 |
| DIN 24° Heavy | |
| DIN 24°H, Female, Swivel - JIC 37°, Male (DHFJ-JCM) | 363 |
| DIN 24°H, Male - JIC 37°, Male (DHM-JCM) | 363 |
| DIN 24° Light | |
| DIN 24°L, Female, Swivel - JIC 37°, Male (DLFX-JCM) | 363 |
| DIN 24°L, Male - JIC 37°, Male (DLM-JCM) | 364 |
| Code 62 | |
| Code 62 - JIC 37°, Male (FH-JCM) | 365 |
| Code 62 - JIC 37°, Male, 45° Elbow (FH-JCM45) | 365 |
| Code 62 - JIC 37°, Male, 90° Elbow (FH-JCM90) | 365 |
| Code 62 - ORFS, Male (FH-OFM) | 366 |
| Code 62 - ORFS, Male, 45° Elbow (FH-OFM45) | 366 |
| Code 62 - ORFS, Male, 90° Elbow (FH-OFM90) | 366 |
| Code 61 | |
| Code 61 - JIC 37°, Male (FL-JCM) | 367 |
| Code 61 - JIC 37°, Male, 45° Elbow (FL-JCM45) | 367 |
| Code 61 - JIC 37°, Male, 90° Elbow (FL-JCM90) | 368 |
| Code 61 - ORFS, Male (FL-OFM) | 368 |
| Code 61 - ORFS, Male, 45° Elbow (FL-OFM45) | 368 |
| Code 61 - ORFS, Male, 90° Elbow (FL-OFM90) | 369 |
| JIC 37° | |
| JIC 37°, Cap (JCC) | 370 |
| JIC 37°, Female - JIC 37°, Male, Reducer/Expander (JCF-JCMRE) | 370 |
| JIC 37°, Female, Bulkhead Lock Nut (JCFBLN) | 371 |
| JIC 37°, Female, Swivel - NPTF, Female (JCFX-NPF) | 372 |
| JIC 37°, Female, Swivel - NPTF, Male (JCFX -NPM) | 372 |
| JIC 37°, Female, Swivel - NPTF, Male, 90° Elbow (JCFX-NPM90) | 373 |
| JIC 37°, Male - JIC 37°, Female, Swivel, (JCM-JCFX) | 373 |
| JIC 37°, Male - JIC 37°, Female, Swivel, 45° Elbow (JCM-JCFX45) | 373 |
| JIC 37°, Male - JIC 37°, Female, Swivel, 90° Elbow (JCM-JCFX90) | 374 |
| JIC 37°, Male - JIC 37°, Female, Swivel - JIC 37°, Male Tee (JCM-JCFX-JCM) | 374 |
| JIC 37°, Male - JIC 37°, Male (JCM-JCM) | 375 |
| JIC 37°, Male - JIC 37°, Male, 90° Elbow (JCM-JCM90) | 375 |
| JIC 37°, Male - JIC 37°, Male - JIC 37°, Female, Swivel Tee (JCM-JCM-JCFX) | 376 |
| JIC 37°, Male - JIC 37°, Male - JIC 37°, Male Tee (JCM-JCM-JCM) | 376 |
| JIC 37°, Male - JIC 37°, Male - NPTF, Male Tee (JCM-JCM-NPM) | 376 |
| JIC 37°, Male - JIC 37°, Male - OR Boss, Male Tee (JCM-JCM-OBM) | 377 |
| JIC 37°, Male - JIC 37°, Male, Bulkhead (JCM-JCMB) | 377 |
| JIC 37°, Male - JIC 37°, Male, Bulkhead, 90° Elbow (JCM-JCMB90) | 378 |
| JIC 37°, Male - Metric Port, Male (JCM-MPM) | 378 |
| JIC 37°, Male - Metric Port, Male, 90° Elbow (JCM-MPM90) | 379 |
| JIC 37°, Male - Metric Standpipe (JCM-MS) | 379 |
| JIC 37°, Male - NPTF, Female (JCM-NPF) | 380 |
| JIC 37°, Male - NPTF, Female, 90° Elbow (JCM-NPF90) | 381 |
| JIC 37°, Male - NPTF, Male (JCM-NPM) | 381 |
| JIC 37°, Male - NPTF, Male, Long (JCM-NPM-L) | 383 |
| JIC 37°, Male - NPTF, Male, Extra Long (JCM-NPM-LL) | 383 |
| JIC 37°, Male - NPTF, Male, 45° Elbow (JCM-NPM45) | 383 |
| JIC 37°, Male - NPTF, Male, 90° Elbow (JCM-NPM90) | 384 |
| JIC 37°, Male - NPTF, Male, 90° Elbow, Long (JCM-NPM90-L) | 385 |
| JIC 37°, Male - NPTF, Male, 90° Elbow, Extra Long (JCM-NPM90-XL) | 386 |
| JIC 37°, Male - NPTF, Male, 90° Elbow, Extra Extra Long (JCM-NPM90-XXL) | 386 |
| JIC 37°, Male - NPTF, Male, Swivel, 90° Elbow (JCM-NPMX90) | 386 |
| JIC 37°, Male - OR Boss, Male (JCM-OBM) | 387 |
| JIC 37°, Male - OR Boss, Male, Long (JCM-OBM-L) | 388 |
| JIC 37°, Male - OR Boss, Male, 45° Elbow (JCM-OBM45) | 389 |
| JIC 37°, Male - OR Boss, Male, 90° Elbow (JCM-OBM90) | 390 |
| JIC 37°, Male - OR Boss, Male, 90° Elbow, Long (JCM -OBM90-L) | 391 |



One Source, One System, One Solution.

www.hydraulics.goodyear.com

Information in this catalog supersedes all previously printed material and is current as of September 2006. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online. Complete product warranty and terms of sale information can be found on the last pages of this catalog.

TABLE OF CONTENTS

| | |
|--|-----|
| JIC 37°, Male - OR Boss, Male, 90° Elbow, Extra Long (JCM-OBM90-XL) | 391 |
| JIC 37°, Male - OR Boss, Male, 90° Elbow, Extra Extra Long (JCM-OBM90-XXL) | 391 |
| JIC 37°, Male - OR Boss, Male - JIC 37°, Male Tee (JCM-OBM-JCM) | 392 |
| JIC 37°, Male - OR Boss, Male, Swivel, 90° Elbow (JCM-OBMX90) | 392 |
| JIC 37°, Male, Bulkhead - NPTF, Male (JCMB-NPM) | 393 |
| JIC 37°, Plug (JCP) | 393 |
| JIC 37°, Tube Nut (JCTN) | 393 |
| JIC 37°, Tube Nut, Long (JCTNL) | 394 |
| JIC 37°, Tube Sleeve (JCTS) | 394 |
| JIS 30° | |
| JIS 30°, Cap (JSC) | 394 |
| JIS 30°, Plug (JSP) | 395 |
| Komatsu 30° Metric | |
| Komatsu 30° Metric, Cap (KMC) | 395 |
| Komatsu 30° Metric, Plug (KMP) | 395 |
| Metric | |
| Metric Compression, Sleeve (MCS) | 396 |
| Metric Heavy, Tube Cap (MHTC) | 396 |
| Metric Heavy, Tube Nut (MHTN) | 396 |
| Metric Heavy, Tube Plug (MHTP) | 397 |
| Metric Light, Tube Cap (MLTC) | 397 |
| Metric Light, Tube Nut (MLTN) | 397 |
| Metric Light, Tube Plug (MLTP) | 398 |
| Metric Port, Hollow Hex Plug (MPHHP) | 398 |
| Metric Port, Plug (MPP) | 398 |
| NPTF | |
| NPTF, Cap (NPC) | 399 |
| NPTF, Female - Metric Port, Male (NPF-MPM) | 399 |
| NPTF, Female - NPTF, Female (NPF-NPF) | 399 |
| NPTF, Female - NPTF, Female, 45° Elbow (NPF-NPF45) | 400 |
| NPTF, Female - NPTF, Female, 90° Elbow (NPF-NPF90) | 400 |
| NPTF, Female - NPTF, Female - NPTF, Female Tee (NPF-NPF-NPF) | 400 |
| NPTF, Female - NPTF, Female - NPTF, Male Tee (NPF-NPF-NPM) | 401 |
| NPTF, Female - NPSM, Female, Swivel (NPF-NSFX) | 401 |
| NPTF, Female - NPSM, Female, Swivel, 45° Elbow (NPF-NSFX45) | 402 |
| NPTF, Female - NPSM, Female, Swivel, 90° Elbow (NPF-NSFX90) | 402 |
| NPTF, Hollow Hex Plug (NPHHP) | 403 |
| NPTF, Male - NPTF, Female, 45° Elbow (NPM-NPF45) | 403 |
| NPTF, Male - NPTF, Female, 90° Elbow (NPM-NPF90) | 403 |
| NPTF, Male - NPTF, Female - NPTF, Female Tee (NPM-NPF-NPF) | 404 |
| NPTF, Male - NPTF, Female, Expander/Extender (NPM-NPFEX) | 404 |
| NPTF, Male - NPTF, Female, Reducer Bushing (NPM-NPFRB) | 405 |
| NPTF, Male - NPTF, Male, 90° Elbow (NPM-NPM90) | 406 |
| NPTF, Male - NPTF, Male, Hex Nipple (NPM-NPMHN) | 406 |
| NPTF, Male - NPTF, Male, Hex Nipple, Long (NPM-NPMHN-L) | 407 |
| NPTF, Male - NPTF, Male, Swivel, 90° Elbow (NPM-NPMX90) | 407 |
| NPTF, Male - NPSM, Female, Swivel (NPM-NSFX) | 408 |
| NPTF, Male - NPSM, Female, Swivel, 45° Elbow (NPM-NSFX45) | 408 |
| NPTF, Male - NPSM, Female, Swivel, 90° Elbow (NPM-NSFX90) | 409 |
| NPTF, Male - NPSM, Female, Swivel, 90° Elbow, Extra Long (NPM-NSFX90-XL) | 410 |
| NPTF, Male, Swivel - NPTF, Female, 90° Elbow (NPMX-NPF90) | 410 |
| NPTF, Plug (NPP) | 410 |
| NPTF, Square Head Plug (NPSHP) | 411 |
| NPSM | |
| NPSM, Female Swivel - NPSM, Female Swivel - NPTF, Male Tee (NSFX-NSFX-NPM) | 411 |
| NPSM, Female Swivel Tee (NSFX-NSFX-NSFX) | 411 |
| O-Ring Boss | |
| OR Boss, Hollow Hex Plug (OBHHP) | 412 |
| OR Boss, Male - NPTF, Female (OBM-NPF) | 412 |
| OR Boss, Male - NPTF, Female, 90° Elbow (OBM-NPF90) | 413 |
| OR Boss, Male - NPTF, Female, 90° Elbow, Long (OBM-NPF90-L) | 414 |
| OR Boss, Male - NPTF, Female, 90° Elbow, Extra Long (OBM-NPF90-XL) | 414 |
| OR Boss, Male - NPTF, Male (OBM-NPM) | 414 |
| OR Boss, Male - NPSM, Female, Swivel (OBM-NSFX) | 415 |
| OR Boss, Male - NPSM, Female, Swivel, 45° Elbow (OBM-NSFX45) | 416 |
| OR Boss, Male - NPSM, Female, Swivel, 90° Elbow (OBM-NSFX90) | 416 |
| OR Boss, Male - OR Boss, Female, Reducer/Expander (OBM-OBFRE) | 417 |
| OR Boss, Plug (OBP) | 418 |
| O-Ring Face Seal | |
| ORFS, Bulkhead Lock Nut (OFBLN) | 418 |
| ORFS, Braze Sleeve (OFBS) | 418 |

TABLE OF CONTENTS

| | |
|---|-----|
| ORFS, Cap (OFC) | 419 |
| ORFS, Female, Swivel - JIC 37°, Male (OFFX - JCM) | 419 |
| ORFS, Male - JIC 37°, Male (OFM-JCM) | 419 |
| ORFS, Male - NPTE, Male (OFM-NPM) | 420 |
| ORFS, Male - NPTE, Male, 90° Elbow (OFM-NPM90) | 420 |
| ORFS, Male - OR Boss, Male (OFM-OBM) | 421 |
| ORFS, Male - OR Boss, Male, Long (OFM-OBM-L) | 421 |
| ORFS, Male - OR Boss, Male, 45° Elbow (OFM-OBM45) | 422 |
| ORFS, Male - OR Boss, Male, 90° Elbow (OFM-OBM90) | 422 |
| ORFS, Male - OR Boss, Male, 90° Elbow, Long (OFM-OBM90-L) | 423 |
| ORFS, Male - OR Boss, Male, 90° Elbow, Extra Long (OFM-OBM90-XL) | 423 |
| ORFS, Male - OR Boss, Male - ORFS Male Tee (OFM-OBM-OFM) | 424 |
| ORFS, Male - ORFS, Female, Swivel, 90° Elbow (OFM-OFFX90) | 424 |
| ORFS, Male - ORFS, Female, Swivel - ORFS, Male Tee (OFM-OFFX-OFM) | 424 |
| ORFS, Male - ORFS, Male (OFM-OFM) | 425 |
| ORFS, Male - ORFS, Male, 90° Elbow (OFM-OFM90) | 425 |
| ORFS, Male - ORFS, Male - OR Boss, Male Tee (OFM-OFM-OBM) | 425 |
| ORFS, Male - ORFS, Male - ORFS, Female, Swivel Tee (OFM-OFM-OFFX) | 426 |
| ORFS, Male - ORFS, Male, Bulkhead (OFM-OFMB) | 426 |
| ORFS, Male - ORFS, Male, Bulkhead, 90° Elbow (OFM-OFMB90) | 426 |
| ORFS, Plug (OFP) | 427 |
| ORFS, Tube Nut (OFTN) | 427 |

BRASS ADAPTERS

(Prefix "B" in Part Number Indicates Brass Adapter)

| | |
|---|-----|
| Compression Tube | |
| Compression Tube (B-CT-CT) | 427 |
| Compression Tube, 90° Elbow (B-CT-CT90) | 428 |
| Compression Tube Tee (B-CT-CT-CT) | 428 |
| Compression Tube, Bulkhead (B-CT-CTB) | 428 |
| Compression Tube Nut (B-CTN) | 429 |
| Compression Tube Sleeve (B-CTS) | 429 |
| NPTE | |
| NPTE, Breather Vent, Plug (B-NPBVP) | 429 |
| NPTE, Cap (B-NPC) | 430 |
| NPTE, Female - Compression Tube (B-NPF-CT) | 430 |
| NPTE, Female - NPTE, Female (B-NPF-NPF) | 431 |
| NPTE, Female - NPTE, Female, 90° Elbow (B-NPF-NPF90) | 431 |
| NPTE, Female Tee (B-NPF-NPF-NPF) | 431 |
| NPTE, Female Cross (B-NPF-NPF-NPF-NPF) | 432 |
| NPTE, Female - NPTE, Female - NPTE, Male Tee (B-NPF-NPF-NPM) | 432 |
| NPTE, Female - NPTE, Female, Bulkhead (B-NPF-NPFB) | 432 |
| NPTE, Female - NPTE, Female, Needle Valve (B-NPF-NPFNV) | 433 |
| NPTE, Female - NPTE, Male - NPTE Female Tee - (B-NPF-NPM-NPF) | 433 |
| NPTE, Hex Head Plug (B-NPHHP) | 433 |
| NPTE, Male - Compression Tube (B-NPM-CT) | 434 |
| NPTE, Male - Compression Tube, 90° Elbow (B-NPM-CT90) | 434 |
| NPTE, Male - NPTE, Female, 45° Elbow (B-NPM-NPF45) | 435 |
| NPTE, Male - NPTE, Female, 90° Elbow, Compact (B-NPM-NPF2W90) | 435 |
| NPTE, Male - NPTE, Female, 90° Elbow (B-NPM-NPF90) | 436 |
| NPTE, Male - NPTE, Female, Expander/Extender - (B-NPM-NPFEX) | 436 |
| NPTE, Male - NPTE, Female, Needle Valve (B-NPM-NPFNV) | 436 |
| NPTE, Male - NPTE, Female, Reducer Bushing (B-NPM-NPFRB) | 437 |
| NPTE, Male - NPTE, Male, 90° Elbow (B-NPM-NPM90) | 437 |
| NPTE, Male - NPTE, Male, Close Nipple (B-NPM-NPMCN) | 437 |
| NPTE, Male - NPTE, Male, Hex Nipple (B-NPM-NPMHN) | 438 |
| NPTE, Male - NPTE, Male, Nipple, Long (B-NPM-NPMN-L) | 438 |
| NPTE, Male, Drain Cock, Angle Bib (B-NPMDCAB) | 439 |
| NPTE, Male, Drain Cock, External Seat (B-NPMDCES) | 439 |
| NPTE, Male, Drain Cock, External Seat (B-NPMDCES) | 439 |
| NPTE, Male, Drain Cock, Internal Seat (B-NPMDCIS) | 440 |
| NPTE, Male, Drain Cock, Internal Seat, Tee Handle (B-NPMDCISTH) | 440 |
| NPTE, Plug (B-NPP) | 440 |
| NPTE, Square Head Plug (B-NPSHP) | 441 |
| NPTE, Slotted Plug (B-NPSP) | 441 |
| SAE 45° Flare | |
| SAE 45°, Cap (B-SFC) | 441 |
| SAE 45°, Male - NPTE, Female (B-SFM-NPF) | 442 |
| SAE 45°, Male - NPTE, Female, 90° Elbow (B-SFM-NPF90) | 442 |
| SAE 45°, Male - NPTE, Male (B-SFM-NPM) | 443 |
| SAE 45°, Male - NPTE, Male, 45° Elbow (B-SFM-NPM45) | 443 |

TABLE OF CONTENTS

| | |
|--|-----|
| SAE 45°, Male - NPTF, Male, 90° Elbow (B-SFM-NPM90) | 444 |
| SAE 45°, Male - NPTF, Male - SAE 45°, Male Tee (B-SFM-NPM-SFM) | 444 |
| SAE 45°, Male - SAE 45°, Male (B-SFM-SFM) | 445 |
| SAE 45°, Male - SAE 45°, Male, 90° Elbow (B-SFM-SFM90) | 445 |
| SAE 45°, Male - SAE 45°, Male - NPTF, Male (B-SFM-SFM-NPM) | 446 |
| SAE 45°, Male Tee (B-SFM-SFM-SFM) | 446 |
| SAE 45°, Male Cross (B-SFM-SFM-SFM-SFM) | 447 |
| SAE 45°, Nut, Long (B-SFNL) | 447 |
| SAE 45°, Nut, Short (B-SFNS) | 447 |
| SAE 45°, Plug (B-SFP) | 448 |
| SAE 45° Inverted Flare | |
| SAE 45° Inverted Flare, Female - NPTF, Female (B-SIF-NPF) | 448 |
| SAE 45° Inverted Flare, Female - NPTF, Male (B-SIF-NPM) | 448 |
| SAE 45° Inverted Flare, Female - SAE 45° Inverted, Female, (B-SIF-SIF) | 449 |
| SAE 45° Inverted Flare, Female - SAE 45° Inverted, Female, 90° Elbow (B-SIF-SIF90) | 449 |
| SAE 45° Inverted Flare, Male Nut (B-SIMN) | 449 |
| SAE 45° Inverted Flare, Plug (B-SIP) | 450 |
| Adapter Specifications and Assembly Instructions | 451 |

Equipment and Accessories

| | |
|-----------------------|-----|
| Crimpers | |
| PC125M | 461 |
| PC125 | 462 |
| PC150 | 463 |
| PC150H | 464 |
| PC200 | 465 |
| PC400 | 466 |
| Saws | |
| SW101 | 467 |
| SW102 | 467 |
| SW103 | 467 |
| Manual Skiving Tool | |
| Holder | 468 |
| External Skiving Tool | 468 |
| Internal Skiving Tool | 470 |
| Cabinets | |
| CB100 | 471 |
| CB101 | 471 |

Assemblies

| | |
|--|-----|
| Selecting the Proper Hose Assembly, S.T.A.M.P.E.D. | 472 |
| Defining Hose and Assembly Length | 474 |
| Steps in Hose Assembly | 476 |
| Steps in Cool Clip Air Conditioning Hose Assembly | 484 |
| Air Conditioning Fitting Crimping Procedures | 485 |

Installation and Maintenance

| | |
|--------------------------------------|-----|
| Service Life Factors | 487 |
| Safety Considerations | 488 |
| Proper Installation and Hose Routing | 489 |
| Hose Maintenance and Storage | 491 |

Appendix

| | |
|----------------------------------|-----|
| Fitting Identification | 493 |
| Fitting identification Templates | 510 |
| Fitting Nuts | 512 |
| Recommended Torque Values | 513 |
| Hose I.D. Selection Nomograph | 514 |
| Hose Pressure Drop | 516 |
| Chemical Resistance Tables | 517 |
| Temperature Conversion Chart | 529 |
| Pressure Conversions | 530 |
| Fractional Equivalents | 531 |
| Conversion Constants | 532 |
| Alphanumeric Index | 533 |

Caterpillar® is the registered trademark of Caterpillar Inc., Peoria, Illinois.

Komatsu® is the registered trademark of Komatsu Ltd., Tokyo, Japan.

GOODYEAR One Source, One System, One Solution.

www.hydraulics.goodyear.com

PROPER ASSEMBLY OF GOODYEAR PERMA-CRIMP™ HOSE AND FITTINGS

Goodyear Perma-Crimp hose, fittings and crimping equipment work together to provide an efficient and reliable hose connection. Goodyear hose and fittings are part of an engineered system, and are to be assembled in accordance with Goodyear specifications. Using non-Goodyear components may produce an assembly that does not meet rated performance. **GOODYEAR DOES NOT WARRANT, EXPRESSLY OR BY IMPLICATION, HOSE ASSEMBLIES THAT DO NOT INCORPORATE GOODYEAR PERMA-CRIMP HOSE AND FITTINGS, OR ARE NOT CRIMPED IN ACCORDANCE WITH GOODYEAR'S PROCESS SPECIFICATIONS.**

Buyers may elect to attach additional or non-standard parts or equipment, or to use different manufacturing specifications, as necessary to meet the requirements of the buyer or customer's application. In such cases, the buyer has sole responsibility to qualify the hose for these applications as necessary to ensure performance capability.

For guidance in the assembly of Goodyear Perma-Crimp hose and couplings, please refer to the Goodyear Crimp Specifications Manual. Information in this catalog is believed to be accurate, but is not warranted, and is subject to change without prior notice. For the most current available product information, check Goodyear's website: www.hydraulics.goodyear.com.